

## T-200 (JACE-200) Data Sheet

### Overview

The Vykon JACE-200™ (Java Application Control Engine) is a compact, embedded controller/server platform. It combines integrated control, supervision, data logging, alarming, scheduling and network management functions with Internet connectivity and web serving capabilities in a small, compact platform. The JACE-200 makes it possible to control and manage external devices over the Internet and present real time information to users in web-based graphical views.

The JACE-200 is a member of the Vykon suite of Javabased controller/server products, software applications and tools, which are designed to integrate a variety of devices and protocols into unified, distributed systems. Vykon products are powered by the revolutionary NiagaraAX Framework®, the industry's first software technology designed to integrate diverse systems and devices into a seamless system. Niagara supports a wide range of protocols including LonWorks™, BACnet™, MODbus, oBIX and Internet standards. The AX Framework also includes integrated network management tools to support the design, configuration, installation and maintenance of interoperable networks.

### Applications

The JACE-200 is ideal for smaller facilities, remote sites, and for distributing control and monitoring throughout large facilities. Optional input/output modules can be plugged in for applications where local control is required. The JACE-200 also supports a wide range of field busses for connection to remote I/O and stand-alone controllers. In small facility applications, the JACE-200 is all you need for a complete system.

The JACE-200 serves data and rich graphical displays to a standard web browser via an Ethernet LAN or remotely over the Internet, or dial-up modem. In larger facilities, multi-building applications and largescale control system integrations, NiagaraAX Supervisor™ software can be used to aggregate information (real-time data, history, alarms, etc.) from large numbers of JACEs into a single unified application. The AX Supervisor can manage global control functions, support data passing over multiple networks, connect to enterprise level software applications, and host multiple, simultaneous client workstations connected over the local network, the Internet, or dial-up modem.



### Features

- » Embedded Power PC platform @ 250 MHz
- » Supports open and legacy protocols
- » Web User interface serves rich presentations and live data to a browser
- » Run stand-alone control, energy management, and multi-protocol integration
- » Standard and optional communications boards
- » Can be expanded with optional 16 and 34 point I/O Modules
- » Small compact design is easy to install and supports multiple power options
- » Optional 16 and 34 point I/O modules

## Specifications

### Platform

PowerPC 405EP 250 MHz processor

64MB SDRAM & 64 MB Serial Flash (optional 128 MB SDRAM)

128 KB Static RAM

Battery Backup - 5 minutes typical - shutdown begins within 10 seconds

Real-time clock - 3 month backup max via battery

#### Platform Options

**NPB-128** - Memory upgrade option. Upgrades JACE-2 to 128 MB SDRAM

### Operating System

GNX RTOS

IBM J9 JVM Java Virtual Machine

NiagaraAX

### Communications

2 Ethernet Ports – 10/100 Mbps (RJ-45 Connectors)

1 RS 232 Port (9 pin D-shell connector)

1 RS 485 non isolated port (3 Screw Connector on base board)

### Optional Communications Cards

**NPB-LON** - Optional 78 Kbps FTT10 A Lon Adapter

**NPB-232** - Optional RS-232 port adapter with 9 pin D-shell connector

**NPB-2X-485** - Optional dual port RS-485 adapter; electrically isolated

### Power Supply

NPB-PWR - Optional: 24 Volt AC/DC power supply module, Din Rail mounted

Optional Wall Power Modules – (Note: All modules are universal input: 90 – 240 volts, 50/60

Hz.; the model numbers below represent the various plug configurations only)

» **WPM-US** - 120 Vac, 50- 60 Hz. US

» **WPM-EU** - 230 Vac, 50-60 Hz. Europe/Asia

» **WPM-UK** - 230 Vac 50-60 Hz. UK

### Chassis

**Construction:** Plastic, din rail or screw mount chassis, plastic cover

**Cooling:** Internal air convection

**Dimensions:** 6.313" (16.04 cm) W x 4.820"(12.24 cm) H (including connectors) x 2.438" (6.19 cm) D

### Environment

**Operating temperature range:** 0° to 50°C (32°F to 122°F)

**Storage Temperature range:** 0° to 60°C (32°F to 140°F)

**Relative humidity range:** 5% to 95%, non-condensing

### Agency Listings

UL 916, C-UL listed to Canadian Standards Association (CSA) C22.2 No. 205-M1983 "Signal Equipment", CE, FCC part 15 Class A, C-tick (Australia)

### Optional I/O Modules

#### IO-34 - 34 Point I/O Module

Max of 1 per Jace-200; includes integral 24 volt AC/DC input power supply for JACE 2 and IO; no other power required

16 Universal Inputs (Type 3 (10k) Thermistors, 0-1000 ohm, 0-10 volts, 0-20 mA with external resistor)

10 relay outputs (Form A contacts, 24 VAC @.5 amp rated

8 analog outputs (0-10 volt DC)

#### IO-16 - 16 Point I/O Module

Up to 4 per Jace-200, 2 per Jace-200 if combined with a 34 Point I/O module

8 Universal Inputs (Type 3 (10k) Thermistors, 0-1000 ohm, 0-10 volts, 0-20 mA with external resistor)

4 relay outputs (Form A contacts, 24 VAC @.5 amp rated

4 analog outputs (0-10 volt DC)